

20KATF05MPN Quick coupling with hose barb





Quick coupling single shut-off, hose barb 5 mm, nominal diameter 2,7, <35 bar, brass nickel plated, seal NBR



Product description

Mini industrial coupling with internationally used profile. Frequent use in medical technology and chemistry/pharmacy. Coupling system with single-hand operation. High flow despite small dimensions plus many applications with a variety of medio.

More images



Product properties

Shut-off	Quick coupling Single Shut-Off
Connection	Hose barb 5 mm
Connection description	Hose barb 5 mm
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	NBR
Seal description	Nitrite-butadiene rubber
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,009
Hydraulics	No
Compatibility	RECTUS 91
Ball locking	Yes
Material	Brass nickel plated
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm²	6
Bore in mm	2,7
Surface	nickel plated
Pneumatics	Yes
Series	20
Series long	20KA
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. Small dimensions.
Water-resistant	Yes
Material connection	Brass nickel plated
Material seal	Perbunan®
Material sleeve	Brass nickel plated
Material spring snap ring	stainless steel AISI 301
Material balls/pins	Stainless steel AISI 420
Material valve	Brass
Material valve body	Brass nickel plated
Two-hand operation	No

Dimensions

Connection A	5 mm
D mm	10
L mm	34
L1 mm	13