

## 27SBIW21MPN Plug with female thread




Plug double shut-off, female thread G 1/2, nominal diameter 10, <35 bar, brass nickel plated, seal NBR



### Product description

1/2 universal industrial coupling with standard European profile for use with large pneumatic consumers. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. The series stands out for its robust design (steel sleeve), extremely high flow and long service life even with the hardest use. The collar design minimises damage to the valve body.

### More images



## Product properties

|                                          |                                                                                                                                  |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Shut-off                                 | Plug Double Shut-Off                                                                                                             |
| Connection                               | Female thread 1/2"                                                                                                               |
| Connection description                   | Female pipe thread of Whitworth form ISO 228 1/2"                                                                                |
| Connection type                          | Female thread                                                                                                                    |
| Suitable breath / respiratory protection | No                                                                                                                               |
| Seal                                     | NBR                                                                                                                              |
| Seal description                         | Nitrite-butadiene rubber                                                                                                         |
| Working pressure                         | 35 bar maximum static working pressure with safety factor 4 to 1.                                                                |
| Pressure eliminator                      | No                                                                                                                               |
| Single-hand operation                    | Yes                                                                                                                              |
| Self-venting coupling                    | No                                                                                                                               |
| Flat-sealing                             | No                                                                                                                               |
| Mould coupling                           | No                                                                                                                               |
| Weight in kg                             | 0,0865                                                                                                                           |
| Hydraulics                               | No                                                                                                                               |
| Ball locking                             | No                                                                                                                               |
| Material                                 | Brass nickel plated                                                                                                              |
| Material description                     | Brass CuZn39Pb3 2.0401 (except sleeve)                                                                                           |
| Bore area in mm <sup>2</sup>             | 80                                                                                                                               |
| Bore in mm                               | 10                                                                                                                               |
| Surface                                  | nickel plated                                                                                                                    |
| Pneumatics                               | Yes                                                                                                                              |
| Series                                   | 27                                                                                                                               |
| Series long                              | 27SB                                                                                                                             |
| Safety locking system                    | No                                                                                                                               |
| Standard product                         | No                                                                                                                               |
| Pin lock                                 | No                                                                                                                               |
| Working temperature                      | -20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) 0°C up to +316°C (FFKM) depending on the medium. |
| Ultra-FLO-valve                          | No                                                                                                                               |
| Vacuum suitable                          | No                                                                                                                               |
| Advantages                               | One-hand operation. Low pressure Drop. UltraFlo valve. The collar design minimises damage to the valve body.                     |
| Water-resistant                          | Yes                                                                                                                              |
| Material connection                      | Brass nickel plated                                                                                                              |
| Material seal                            | Perbunan®                                                                                                                        |
| Material spring snap ring                | stainless steel AISI 301                                                                                                         |
| Material valve                           | Brass                                                                                                                            |
| Two-hand operation                       | No                                                                                                                               |

## Dimensions

|              |       |
|--------------|-------|
| Connection A | G 1/2 |
| L mm         | 54,5  |
| L1 mm        | 12    |
| SW mm        | 24    |