

37SFTF13SXN Plug with hose barb





Plug straight-through, hose barb 13mm (1/2), nominal diameter 11, <35 bar, steel nickel plated



Product description

Robust brass coupling system 1/2 according to ISO 6150 B and US MIL-SPEC 4109. Coupling system with single-hand operation. The high insertion depth is guaranteed by an optimised plug guide.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Hose barb 13mm LW(1/2")
Connection description	Hose barb 13mm LW(1/2")
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,0447
Hydraulics	No
Compatibility	INDUSTRIAL INTERCHANGE 1/2" US-MIL-NORM-C-4109 1/2" ISO 6150-B-17
Ball locking	No
Material	Steel nickel-plated
Material description	Steel 9SMnPb28K 1.0718
Bore area in mm ²	95
Bore in mm	11
Surface	nickel plated
Pneumatics	Yes
Series	37
Series long	37SF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. Robust structure.
Water-resistant	No
Two-hand operation	No

Dimensions

Connection A	13 mm
D mm	17
L mm	62
L1 mm	25