

73KBIW17MEX Quick coupling with female thread




Quick coupling double shut-off, female thread G 3/8, nominal diameter 7,5, <200 bar, brass, seal EPDM



Product description

Coupling series 73kb with plug profile compliant with ISO 7241-1 series B. Particularly suited to use with liquid medio. Coupling system with two-hand operation, i.e. both hands are required when coupling/uncoupling. The coupling series stands out for its high flow rates against a low pressure drop.

More images



Product properties

Shut-off	Quick coupling Double Shut-Off
Connection	Female thread 3/8"
Connection description	Female pipe thread of Whitworth form ISO 228 3/8"
Connection type	Female thread
Suitable breath / respiratory protection	Yes
Seal	EPDM
Seal description	Ethylene-propylene-diene rubber
Working pressure	PB = 200 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	No
Self-venting coupling	No
Flat-sealing	No
Mould coupling	Yes
Weight in kg	0,2258
Hydraulics	No
Ball locking	Yes
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm²	44
Bore in mm	7,5
Surface	blank finish
Pneumatics	Yes
Professional recommendation	Water
Series	73
Series long	73KB
Safety locking system	No
Standard product	Yes
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	Particularly suited to use with liquid medio. Double O-ring sealing.
Water-resistant	Yes
Material connection	Brass
Material sleeve	Brass
Material spring snap ring	stainless steel AISI 301
Material balls/pins	Stainless steel AISI 420
Material valve	Brass
Material valve body	Brass
Two-hand operation	Yes

Dimensions

Connection A	G 3/8
D mm	35
L mm	64
L1 mm	11,5
SW mm	22