

7511 V Quick coupling




Hydraulic quick coupling double shut-off with pressure eliminator, female thread G 3/4, nominal diameter 20, 280 bar, brass, seal FKM



Product description

The TEMA Standard Series is characterised by a low pressure drop and maximum flow capacity. The coupling system is available as double shut-off or straight through version. The 2500 can be used also as a single shut-off version.

More images



Product properties

Shut-off	Quick coupling Double Shut-Off
Connection	Female thread 3/4"
Connection type	Female thread
Coupled working pressure in bar	280
Seal	FKM
Pressure eliminator	Yes
Single-hand operation	Yes
Flat-sealing	No
Weight in kg	0,585
Size in general	3/4"
Hydraulics	Yes
Ball locking	Yes
Material	Brass
Bore area in mm²	314
Bore in mm	20
Surface	nickel plated and chrome plated
Professional recommendation	Hydraulics
Series	T
Series long	7500
Safety locking system	Yes
Working temperature	-30°C up to +100°C (NBR) -25°C up to +200°C (FKM) depending on the medium.
Vacuum suitable	No
Valve	with
Advantages	Hoher Durchfluss – minimaler Druckabfall. Doppelte Sicherheit durch doppelte O-Ring-Abdichtung. Sicherheits-Schließring verhindert ungewolltes Entkuppeln. Korrosionsbeständig. Kleine Dimensionen.
Material sleeve	Steel hardened, zinc-plated, passivated, sealed
Material spring snap ring	1.4310
Material balls/pins	1.3541
Material locking collar	Messing, Zink-Eisen beschichtet, schwarz passiviert, versiegelt
Material valve	Brass
Material valve holder	Brass
Material valve body	Brass
Two-hand operation	No

Dimensions

Connection A	G 3/4"
D mm	52
L mm	72
SW mm	38