

Filter regulator Syntesi - 5624B244

Filter regulator Syntesi, connection G 1/2", flow rate 4300 l/min., degree of filtration 20 µm, maximum inlet pressure 13 bar



Product description

One unit for filtration, condensate separation and pressure regulation.

Adjusted pressure stays constant despite pressure variations.

360° viewing glass.


Relief valve.

Padlockable push-lock knob.

Including pressure gauge.

Additional ports for pressure gauges, pressure switches or for use as additional air take-off.

More images



Product properties

Shielding plate	Technopolymer
Shut off plate adjustment knob	Steel, galvanized
Connection	Female thread G 1/2"
Seals	NBR O-Ring
Flow rate in l/min	4300
Input and output socket	Brass Ms58 or aluminum, anodized
Adjustment knob	Technopolymer
Filter element	HDPE sintered
Filterfeinheit in µm	20
Filter case	Technopolymer
Flange	Technopolymer
Weight in kg	0,619
Bell	Technopolymer
Transparent container	Technopolymer
max. inlet pressure	13
Board	Technopolymer
Regulator spring	Steel
Regulator screw	Brass Ms58
Ring nut	Technopolymer
Series	Syntesi
Tappet	Technopolymer
Valve	Messing Ms58 vulcanized with NBR
Valve spring	Stainless steel
Centrifuge	Technopolymer

Dimensions

A	61
B	246
C	61
D	70,5
E	47,5
F	38,2
G	Hole for screws M5
I	22,5
L	M38x2
M	178
N	139,8
O	245
P	1/4" (Pressure gauge connection or additional air intake)