

GE-M-ED Male Stud Connector Galvanized Steel

Male metric thread – ED (ISO 9974) / EO 24° cone end, male stud connector, galvanized steel, complete fitting



Product description

The main function of Ermeto DIN male stud high pressure hydraulic tube fittings is to connect different numbers of tubes or hoses. This broad range of fittings, types GEO, GE-M-ED, GE-R-ED up to GE-M is available in steel and in a stainless steel version. Depending on the specific application, these fittings can be delivered with cutting ring (EO-PSR or DPR) or elastomeric seal (EO-2).

Markets:

- Automotive
- Defence
- Energy
- Environment
- Industrial
- Infrastructure
- Machine Tools
- Materials Handling
- Mobile
- Oil and Gas
- Power Generation
- Process
- Transportation
- Water


Applications:

- Suitable for general hydraulic applications.

Features/ benefits:

- Steel and Stainless steel fittings have a high corrosion resistance to aggressive media and environmental influences. These features extend the range of applications.
- High pressure: Ermeto DIN male stud high pressure hydraulic tube fittings have pressure ratings of up to 800 bar (S series) and 500 bar (L series), so that the fittings can be used in a wide range of applications.

More images



Product properties

Series	Light, heavy
Specifications met	DIN ISO 8434
Material	Galvanized steel
Maximum working pressure in bar	250-800
Optional accessories	Pre-assembled with nut and EO-PSR cutting ring
Rohr Außendurchmesser	6-42 mm
Working temperature	-40°C up to 250°C

Dimensions