

D2 6,3mm Inert gas 0069-0410

Plug straight-through, coded system, hose barb 6mm (1/4), Inert gas, <20 bar, stainless steel



Product description

Type D2 for tapping point or in-hose


The coupling pin D2 according to EN561, ISO 7289:

- no mixing up by different coding of coupling pins
- prevents accidental disconnection
- coupling pin in stainless steel

Safety elements of the IBEDA Coupling pin D2:

- coding of coupling pins

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Hose barb 6mm LW(1/4")
Connection type	Hose barb
Flat-sealing	No
Mould coupling	No
Gas types	Acetylene (A), Hydrogen (H), Industrial Gas (C), Natural Gas (Methane M), Propane (P), Oxygen (O), Compressed Air (D), Nitrogen (N), Carbon Dioxide (N), Argon (N) , Helium (N)
Weight in kg	0,017
Hydraulics	No
Coded	Yes
Material	Stainless steel
Maximum working pressure in bar	1,5 (A), 20 (H, C, M, P, O, D, N)
Surface	blank finish
Professional recommendation	Gas safety technology, Coding
Series	D
Series long	D2
Standard product	No
Working temperature	-20°C up to +70°C
Water-resistant	No
Material connection	Edelstahl
Additional information	Zulassungen / Technische Regeln / Richtlinien
Item number	0069-0410

Dimensions

Diameter in mm	12,3
Length in mm	55