

D4 G1/4RH Inert gas 0069-4221

Plug straight-through, coded system, male thread G 1/4RH, Inert gas, <20 bar, stainless steel



Product description

Type D4 for tapping point or in-hose


The coupling pin D4 according to EN561, ISO 7289:

- no mixing up by different coding of coupling pins
- prevents accidental disconnection
- coupling pin in stainless steel

Safety elements of the IBEDA Coupling pin D4:

- coding of coupling pins

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Male thread G 1/4RH
Connection description	Right-hand thread
Connection type	Male thread
Flat-sealing	No
Mould coupling	No
Gas types	Oxygen (O), Compressed Air (D), Nitrogen (N), Carbon Dioxide (N), Argon (N), Helium (N)
Weight in kg	0,029
Hydraulics	No
Coded	Yes
Material	Stainless steel
Maximum working pressure in bar	20 (O, D, N)
Surface	blank finish
Professional recommendation	Gas safety technology, Coding
Series	D
Series long	D4
Standard product	No
Working temperature	-20°C up to +70°C
Water-resistant	No
Material connection	Edelstahl
Additional information	Zulassungen / Technische Regeln / Richtlinien
Item number	0069-4221

Dimensions

Diameter in mm	17
Length in mm	46,5