

DKG-W G3/8LH Fuel gas 3000-1320

Quick coupling single shut-off, coded system, male thread G3/8LH, Fuel gas, <20 bar, brass, pull-System



Product description

Type DKG and DKG-W for in-hose or torch side connection

The quick-action coupling DKG according to EN561, ISO 7289:

- safe interruption of gas flow by automatic gas cut-off when disconnecting
- no mixing up by different coding of coupling pins
- prevents accidental disconnection
- all metal components in brass 2.0401 / spring 1.4310





Safety elements of the IBEDA quick-action coupling DKG:

- SV Shut-off valve

Pull-system

Pull-System-Icon.png

More images



Product properties

Shut-off	Quick coupling Single Shut-Off
Connection	Male thread G 3/8LH
Connection description	Left-hand thread
Connection type	Male thread
Flat-sealing	No
Mould coupling	No
Gas types	Acetylene (A), Hydrogen (H), Industrial Gas (C), Natural Gas (Methane M), Propane (P)
Weight in kg	0,086
Hydraulics	No
Coded	Yes
Material	Brass
Material description	Brass 2.0401
Maximum working pressure in bar	1,5 (A), 20 (H, C, M, P)
Surface	blank finish
Professional recommendation	Gas safety technology, Coding
Series	D
Series long	DKG-W
Standard product	No
Working temperature	-20°C up to +70°C (Oxygen -20°C up to +60°C)
Water-resistant	No
Material connection	Brass
Material sleeve	Brass
Material spring	Stainless steel
Additional information	Zulassungen / Technische Regeln / Richtlinien
Item number	3000-1320

Dimensions

Diameter in mm	21
Length in mm	54