

## 0180 05 00 Plug with hose barb

Plug straight-through, hose barb 5mm, nominal diameter 3, <20 bar, brass nickel plated




### Product description

The one-way shut-off mini series offers a space-saving solution for frequent connection and disconnection of hoses and pneumatic connections.

- Compact construction and ergonomic design
- Color coding: recognizing the circuits at a glance
- Easy uncoupling / one-handed operation

### More images



Product properties

|                                    |                              |
|------------------------------------|------------------------------|
| Shut-off                           | Plug Straight-Through        |
| Connection                         | Hose barb 5 mm               |
| Connection description             | Hose barb for flexible hoses |
| Connection type                    | Hose barb                    |
| Flow rate in l/min                 | 165 (air)                    |
| Weight in kg                       | 0,007                        |
| Material                           | Brass nickel plated          |
| Maximum working pressure in bar    | 20                           |
| Bore in mm                         | 3                            |
| Surface                            | nickel plated                |
| Connection tube outside diameter 2 | 5                            |
| Connection tube outside diameter 3 | 6,5                          |
| RoHS compliant                     | Yes                          |
| Series                             | Mini                         |
| Series long                        | Mini                         |
| Working temperature                | -20°C to +60°C (NBR)         |
| Material connection                | Brass nickel plated          |

Dimensions

|     |     |
|-----|-----|
| L   | 19  |
| ØD  | 5   |
| ØD1 | 6,5 |