

## 2295 12 12 Plug with hose barb

Plug straight-through, hose barb 12mm, nominal diameter 12, <20 bar, brass nickel plated




### Product description

The Medium series is particularly suitable for water and compressed air applications. The wide range of connectors allows many combination options for the end user.

- Designed to transport water and liquids
- High flow capability
- Maximum energy efficiency

### More images



Product properties

|                                    |                          |
|------------------------------------|--------------------------|
| Shut-off                           | Plug Straight-Through    |
| Connection                         | Hose barb 12mm           |
| Connection type                    | Hose barb                |
| Flow rate in l/min                 | 2.200 (air)              |
| Weight in kg                       | 0,014                    |
| Material                           | Brass nickel plated      |
| Maximum working pressure in bar    | 20                       |
| Bore in mm                         | 12                       |
| Surface                            | nickel plated            |
| Connection tube outside diameter 2 | 12                       |
| Connection tube outside diameter 3 | 13,5                     |
| RoHS compliant                     | Yes                      |
| Series                             | Medium                   |
| Series long                        | Medium                   |
| Working temperature                | -20°C up to +100°C (NBR) |
| Material connection                | Brass nickel plated      |

Dimensions

|     |      |
|-----|------|
| G   | 17   |
| L   | 48   |
| L1  | 27   |
| ØD  | 12   |
| ØD1 | 13,5 |