

## 2296 12 27 Plug with female thread

Plug straight-through, female thread G 3/4, nominal diameter 12, <20 bar, brass nickel plated




### Product description

The Medium series is particularly suitable for water and compressed air applications. The wide range of connectors allows many combination options for the end user.

- Designed to transport water and liquids
- High flow capability
- Maximum energy efficiency

### More images



#### Product properties

|                                        |                          |
|----------------------------------------|--------------------------|
| <b>Shut-off</b>                        | Plug Straight-Through    |
| <b>Connection</b>                      | Female thread G 3/4      |
| <b>Connection description</b>          | Female thread BSPP       |
| <b>Connection type</b>                 | Female thread            |
| <b>Flow rate in l/min</b>              | 2.200 (air)              |
| <b>Weight in kg</b>                    | 0,058                    |
| <b>Material</b>                        | Brass nickel plated      |
| <b>Maximum working pressure in bar</b> | 20                       |
| <b>Bore in mm</b>                      | 12                       |
| <b>Surface</b>                         | nickel plated            |
| <b>RoHS compliant</b>                  | Yes                      |
| <b>Series</b>                          | Medium                   |
| <b>Series long</b>                     | Medium                   |
| <b>Working temperature</b>             | -20°C up to +100°C (NBR) |
| <b>Material connection</b>             | Brass nickel plated      |

#### Dimensions

|                          |        |
|--------------------------|--------|
| <b>C</b>                 | G 3/4" |
| <b>E</b>                 | 11     |
| <b>G</b>                 | 30     |
| <b>Size connection 1</b> | G3/4   |
| <b>L</b>                 | 38     |