

## 2511 12 19 Quick coupling with hose barb

Quick coupling single shut-off, hose barb 19mm, nominal diameter 12, <20 bar, brass nickel plated, seal NBR




### Product description

The Medium series is particularly suitable for water and compressed air applications. The wide range of connectors allows many combination options for the end user.

- Designed to transport water and liquids
- High flow capability
- Maximum energy efficiency

### More images



#### Product properties

|                                           |                                |
|-------------------------------------------|--------------------------------|
| <b>Shut-off</b>                           | Quick coupling Single Shut-Off |
| <b>Connection</b>                         | Hose barb 19 mm                |
| <b>Connection type</b>                    | Hose barb                      |
| <b>Seal</b>                               | NBR                            |
| <b>Seal description</b>                   | Nitrite-butadiene rubber       |
| <b>Flow rate in l/min</b>                 | 2.200 (air)                    |
| <b>Weight in kg</b>                       | 0,1656                         |
| <b>Material</b>                           | Brass nickel plated            |
| <b>Maximum working pressure in bar</b>    | 20                             |
| <b>Bore in mm</b>                         | 12                             |
| <b>Surface</b>                            | nickel plated                  |
| <b>Connection tube outside diameter 2</b> | 19                             |
| <b>Connection tube outside diameter 3</b> | 20,5                           |
| <b>RoHS compliant</b>                     | Yes                            |
| <b>Series</b>                             | Medium                         |
| <b>Series long</b>                        | Medium                         |
| <b>Working temperature</b>                | -20°C up to +100°C (NBR)       |
| <b>Material connection</b>                | Brass nickel plated            |
| <b>Material seal</b>                      | NBR                            |

#### Dimensions

|            |      |
|------------|------|
| <b>G</b>   | 29   |
| <b>L</b>   | 81   |
| <b>L1</b>  | 38   |
| <b>ØD</b>  | 19   |
| <b>ØD1</b> | 20,5 |