

## 2297 18 20 Quick coupling with hose barb

Quick coupling straight-through, hose barb 19mm, nominal diameter 19, <20 bar, brass nickel plated, seal NBR




### Product description

The robust Maxi Series is designed for high flow applications and is suitable for compressed air and water.

- Designed to transport water and liquids
- Very high flow rate
- Ideal for water applications

### More images



#### Product properties

|                                           |                                 |
|-------------------------------------------|---------------------------------|
| <b>Shut-off</b>                           | Quick coupling Straight-Through |
| <b>Connection</b>                         | Hose barb 19 mm                 |
| <b>Connection type</b>                    | Hose barb                       |
| <b>Seal</b>                               | NBR                             |
| <b>Seal description</b>                   | Nitrite-butadiene rubber        |
| <b>Flow rate in l/min</b>                 | 8.500 (air)                     |
| <b>Weight in kg</b>                       | 0,18                            |
| <b>Material</b>                           | Brass nickel plated             |
| <b>Maximum working pressure in bar</b>    | 20                              |
| <b>Bore in mm</b>                         | 19                              |
| <b>Surface</b>                            | nickel plated                   |
| <b>Connection tube outside diameter 2</b> | 19                              |
| <b>Connection tube outside diameter 3</b> | 20,7                            |
| <b>RoHS compliant</b>                     | Yes                             |
| <b>Series</b>                             | Maxi                            |
| <b>Series long</b>                        | Maxi                            |
| <b>Working temperature</b>                | -20°C up to +100°C (NBR)        |
| <b>Material connection</b>                | Brass nickel plated             |
| <b>Material seal</b>                      | NBR                             |

#### Dimensions

|            |      |
|------------|------|
| <b>G</b>   | 39,5 |
| <b>L</b>   | 69   |
| <b>L1</b>  | 37   |
| <b>ØD</b>  | 19   |
| <b>ØD1</b> | 20,7 |