

9416A06 13 Quick coupling self-venting


Safety coupling with a self-venting system, female thread G 1/4, bulkhead mountable, nominal diameter 5,5, <16 bar, engineered polymer, seal NBR



Product description

Safety couplings made of polymer with a rotating mechanism help to protect people and machines. The couplings are available in three standard profiles and are therefore perfect for almost any application.

More images



Product properties

Shut-off	Quick coupling Self-Venting system
Connection	Female thread G 1/4
Connection description	Bulkhead mountable female thread BSPP
Connection type	Female thread
Seal	NBR
Seal description	Nitrite-butadiene rubber
Flow rate in l/min	1.250 (air)
Weight in kg	0,135
Compatibility	ARO profile with self-venting
Material	Engineered polymer
Maximum working pressure in bar	16
Bore in mm	5,5
Surface	nickel plated
ØT min	18,5
RoHS compliant	Yes
Series	C9000
Series long	C9000
Working temperature	-20°C to +60°C (NBR)
Material connection	Brass nickel plated
Material seal	NBR
Material sleeve	Plastic
Material balls	Stainless steel
Additional information	Bulkhead mountable

Dimensions

C	G 1/4"
E	12
F	22
G	31,5
Size connection 1	G1/4
K	6
L1	12,5
L2	66,5