

9416E07 17 Quick coupling self-venting


Safety coupling with a self-venting system, female thread G 3/8, bulkhead mountable, nominal diameter 7,2, <16 bar, engineered polymer, seal NBR



Product description

Safety couplings made of polymer with a rotating mechanism help to protect people and machines. The couplings are available in three standard profiles and are therefore perfect for almost any application.

More images



Product properties

Shut-off	Quick coupling Self-Venting system
Connection	Female thread G 3/8
Connection description	Bulkhead mountable female thread BSPP
Connection type	Female thread
Seal	NBR
Seal description	Nitrite-butadiene rubber
Flow rate in l/min	2.000 (air)
Weight in kg	0,153
Compatibility	EURO Profile
Material	Engineered polymer
Maximum working pressure in bar	16
Bore in mm	7,2
Surface	nickel plated
ØT min	22,5
RoHS compliant	Yes
Series	C9000
Series long	C9000
Working temperature	-20°C to +60°C (NBR)
Material connection	Brass nickel plated
Material seal	NBR
Material sleeve	Plastic
Material balls	Stainless steel
Additional information	Bulkhead mountable

Dimensions

C	G 3/8"
E	12
F	24
G	36,5
Size connection 1	G3/8
K max	7
L1	14,5
L2	74