

## 9087U06 21 Plug with male thread


Plug straight-through, male thread G 1/2, nominal diameter 5,5, <16 bar, galvanized steel



### Product description

Safety couplings made of polymer with a rotating mechanism help to protect people and machines. The couplings are available in three standard profiles and are therefore perfect for almost any application.

### More images



Product properties

|                                 |                                 |
|---------------------------------|---------------------------------|
| Shut-off                        | Plug Straight-Through           |
| Connection                      | Male thread G 1/2               |
| Connection description          | Male thread BSPP                |
| Connection type                 | Male thread                     |
| Flow rate in l/min              | 1.250 (air)                     |
| Weight in kg                    | 0,05                            |
| Compatibility                   | ISO B profile with self-venting |
| Material                        | Steel nickel-plated             |
| Maximum working pressure in bar | 16                              |
| Bore in mm                      | 5,5                             |
| Surface                         | nickel plated                   |
| RoHS compliant                  | Yes                             |
| Series                          | C9000                           |
| Series long                     | C9000                           |
| Working temperature             | -20°C to +60°C (NBR)            |
| Material connection             | Steel nickel-plated             |

Dimensions

|                   |        |
|-------------------|--------|
| C                 | G 1/2" |
| E                 | 9      |
| F                 | 24     |
| Size connection 1 | G1/2   |
| L                 | 39     |
| L1                | 24     |