

## 9440U06 17 Manifold with quick couplings


Safety coupling with a self-venting system, female thread G 3/8, nominal diameter 5,5, <16 bar, engineered polymer, seal NBR



### Product description

Safety couplings made of polymer with a rotating mechanism help to protect people and machines. The couplings are available in three standard profiles and are therefore perfect for almost any application.

### More images



#### Product properties

|                                        |                                     |
|----------------------------------------|-------------------------------------|
| <b>Shut-off</b>                        | Quick coupling Self-Venting system  |
| <b>Connection</b>                      | Female thread G 3/8                 |
| <b>Connection description</b>          | Female thread BSPP                  |
| <b>Connection type</b>                 | Female thread                       |
| <b>Seal</b>                            | NBR                                 |
| <b>Seal description</b>                | Nitrite-butadiene rubber            |
| <b>Flow rate in l/min</b>              | 1.250 (air)                         |
| <b>Weight in kg</b>                    | 0,206                               |
| <b>Compatibility</b>                   | ISO B profile with self-venting (Y) |
| <b>Material</b>                        | Engineered polymer                  |
| <b>Maximum working pressure in bar</b> | 16                                  |
| <b>Bore in mm</b>                      | 5,5                                 |
| <b>Surface</b>                         | nickel plated                       |
| <b>RoHS compliant</b>                  | Yes                                 |
| <b>Series</b>                          | C9000                               |
| <b>Series long</b>                     | C9000                               |
| <b>Working temperature</b>             | -20°C to +60°C (NBR)                |
| <b>Material connection</b>             | Brass nickel plated                 |
| <b>Material seal</b>                   | NBR                                 |
| <b>Material sleeve</b>                 | Plastic                             |
| <b>Material balls</b>                  | Stainless steel                     |

#### Dimensions

|                          |        |
|--------------------------|--------|
| <b>C</b>                 | G 3/8" |
| <b>E</b>                 | 11,5   |
| <b>F</b>                 | 19     |
| <b>F1</b>                | 20     |
| <b>G</b>                 | 31,5   |
| <b>Size connection 1</b> | G3/8   |
| <b>H</b>                 | 70     |
| <b>H1</b>                | 16     |