

52SBTF13SPN Plug with hose barb




Plug double shut-off, hose barb 13mm (1/2), nominal diameter 6, <50 bar, steel nickel plated, seal NBR



Product description

Coupling system with German industrial profile. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. Robust coupling in slim design mainly for pneumatic applications. The steel sleeve counters oscillating forces. The high insertion depth is guaranteed by an optimised plug guide.

More images



Product properties

Shut-off	Plug Double Shut-Off
Connection	Hose barb 13mm LW(1/2")
Connection description	Hose barb 13mm LW(1/2")
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	NBR
Seal description	Nitrite-butadiene rubber
Working pressure	PB = 50 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,0627
Hydraulics	No
Ball locking	No
Material	Steel nickel-plated
Material description	Steel 9SMnPb28K 1.0718
Bore area in mm²	30
Bore in mm	6
Surface	nickel plated
Pneumatics	Yes
Series	52
Series long	52SB
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	Single handed operation. Ergonomic design. High flow valve.
Water-resistant	No
Material seal	Perbunan®
Two-hand operation	No

Dimensions

Connection A	13 mm
L mm	77,5
L1 mm	25
SW mm	21