

25SFIW17SXZ Plug with female thread




Plug straight-through, female thread G 3/8, nominal diameter 7,8, <35 bar, steel zinc plated



Product description

Universal industrial coupling with standard European profile. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. The series stands out for its robust design and long service life even with the harshest use.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Female thread 3/8"
Connection description	Female pipe thread of Whitworth form ISO 228 3/8"
Connection type	Female thread
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,023
Hydraulics	No
Compatibility	RECTUS 26 RECTUS 1600/1625 TEMA 1600
Ball locking	No
Material	Galvanized steel
Material description	Steel 9SMnPb28K 1.0718
Bore area in mm²	48
Bore in mm	7,8
Surface	zinc plated
Pneumatics	Yes
Series	25
Series long	25SF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	No
Advantages	One-hand operation. Robust structure. UltraFlo valve.
Water-resistant	No
Two-hand operation	No

Dimensions

Connection A	G 3/8
L mm	39,5
L1 mm	12
SW mm	19