

26SFKK06MXN Plug with hose nut and spring guard



Plug straight-through, with hose nut and spring guard 4 x 6 mm, nominal diameter 7,2, <35 bar, brass nickel plated



Product description

Universal brass coupling with European standard industrial profile. Coupling system with single-hand operation and standard-valve. Small mass size. The ergonomicsleeve design prevents dirt on the valve body.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Tube nut with spring guard 4 x 6 mm
Connection description	Tube nut with spring guard 4 x 6 mm
Connection type	Connection nut
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,0268
Hydraulics	No
Compatibility	RECTUS 25 RECTUS 1600/1625 TEMA 1600
Ball locking	No
Material	Brass nickel plated
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	40
Bore in mm	7,2
Surface	nickel plated
Pneumatics	Yes
Series	26
Series long	26SF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. European standard.
Water-resistant	Yes
Two-hand operation	No

Dimensions

Connection A	4 x 6 mm
D mm	12
G mm	M 10 x 1
L mm	120
L1 mm	7
L2 mm	6