

26SFTF13MXX Plug with hose barb




Plug straight-through, hose barb 13mm (1/2), nominal diameter 7,2, <35 bar, brass



Product description

Universal brass coupling with European standard industrial profile. Coupling system with single-hand operation and standard-valve. Small mass size. The ergonomicsleeve design prevents dirt on the valve body.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Hose barb 13mm LW(1/2")
Connection description	Hose barb 13mm LW(1/2")
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,0215
Hydraulics	No
Compatibility	RECTUS 25 RECTUS 1600/1625 TEMA 1600
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm²	40
Bore in mm	7,2
Surface	blank finish
Pneumatics	Yes
Professional recommendation	Pneumatic standard
Series	26
Series long	26SF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. European standard.
Water-resistant	Yes
Two-hand operation	No

Dimensions

Connection A	13 mm
D mm	12, 15
L mm	48
L1 mm	25