

26KFTF10MPX Quick coupling with hose barb


Quick coupling straight-through, hose barb 10mm, nominal diameter 7,2, <35 bar, brass, seal NBR



Product description

Universal brass coupling with European standard industrial profile. Coupling system with single-hand operation and standard-valve. Small mass size. The ergonomic sleeve design prevents dirt on the valve body.

More images



Product properties

Shut-off	Quick coupling Straight-Through
Connection	Hose barb 10mm
Connection description	Hose barb 10mm
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	NBR
Seal description	Nitrite-butadiene rubber
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,0723
Hydraulics	No
Compatibility	RECTUS 25 RECTUS 1600/1625 TEMA 1600
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	40
Bore in mm	7,2
Surface	blank finish
Pneumatics	Yes
Series	26
Series long	26KF
Safety locking system	No
Standard product	No
Pin lock	Yes
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. European standard.
Water-resistant	Yes
Material connection	Brass
Material seal	Perbunan®
Material sleeve	Brass
Material spring snap ring	Stainless steel AISI 301, hardened
Material balls/pins	Stainless steel AISI 420, hardened
Material valve body	Brass
Two-hand operation	No

Dimensions

Connection A	10 mm
D mm	25
L mm	58
L1 mm	25
SW mm	21