

21SSTF06MXX Plug with hose barb




Plug safety straight through, hose barb 6mm (1/4), nominal diameter 5, <35 bar, brass



Product description

Mini industrial coupling with the world's most popular profile in this nominal diameter. Above average flow performance for liquid and gaseous medio. It also uses an additional safety locking system. This prevents unintentional disconnection. When being disconnected, the plug must first be pushed further into the coupling before it can be disconnected.

More images



Product properties

Shut-off	Plug Safety (straight-through)
Connection	Hose barb 6mm LW(1/4")
Connection description	Hose barb 6mm LW(1/4")
Connection type	Hose barb
Suitable breath / respiratory protection	Yes
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	No
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,007
Hydraulics	No
Compatibility	RECTUS 90
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	20
Bore in mm	5
Surface	blank finish
Pneumatics	Yes
Professional recommendation	Breathing protection
Series	21
Series long	21SS
Safety locking system	Yes
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) 0°C up to +316°C (FFKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	Small dimensions. Safety lock prevents accidental disconnection.
Water-resistant	Yes
Material connection	Brass
Material spring snap ring	stainless steel AISI 301
Material valve	Brass
Two-hand operation	Yes

Dimensions

Connection A	6 mm
D mm	9
L mm	32
L1 mm	17