

20SFAW10MXX Plug with male thread


Plug straight-through, male thread G 1/8, nominal diameter 2,7, <35 bar, brass



Product description

Mini industrial coupling with internationally used profile. Frequent use in medical technology and chemistry/pharmacy. Coupling system with single-hand operation. High flow despite small dimensions plus many applications with a variety of medio.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Male thread 1/8"
Connection description	Male pipe thread of Whitworth form ISO 228 1/8"
Connection type	Male thread
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,005
Hydraulics	No
Compatibility	RECTUS 91
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	6
Bore in mm	2,7
Surface	blank finish
Pneumatics	Yes
Professional recommendation	Pneumatic standard
Series	20
Series long	20SF
Safety locking system	No
Standard product	Yes
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. Small dimensions.
Water-resistant	Yes
Two-hand operation	No

Dimensions

Connection A	G 1/8
L mm	20
L1 mm	7
SW mm	11