

2310 RFV Quick coupling




Hydraulic quick coupling double shut-off, female thread G 1/8, nominal diameter 5, 200 bar, stainless steel AISI 316 L, seal FKM



Product description

The TEMA Standard Series is characterised by a low pressure drop and maximum flow capacity. The coupling system is available as double shut-off or straight through version. The 2500 can be used also as a single shut-off version.

More images



Product properties

Shut-off	Quick coupling Double Shut-Off
Connection	Female thread 1/8"
Connection type	Female thread
Coupled working pressure in bar	200
Seal	FKM
Pressure eliminator	No
Single-hand operation	Yes
Flat-sealing	No
Weight in kg	0,043
Size in general	1/8"
Hydraulics	Yes
Ball locking	Yes
Material	stainless steel AISI 316 L
Bore area in mm²	20
Bore in mm	5
Professional recommendation	Hydraulics
Series	T
Series long	2300
Safety locking system	Yes
Working temperature	-30°C up to +100°C (NBR) -25°C up to +200°C (FKM) depending on the medium.
Vacuum suitable	No
Valve	with
Advantages	Hoher Durchfluss – minimaler Druckabfall. Hoher Betriebsdruck. Korrosionsbeständig. Kleine Dimensionen.
Material sleeve	1.4404
Material spring snap ring	1.4310
Material balls/pins	1.3541
Material locking collar	1.4404
Material valve	Brass
Material valve holder	1.4404
Material valve body	1.4404
Two-hand operation	No

Dimensions

Connection A	G 1/8"
D mm	18
L mm	38
SW mm	15