

## 3100 10 00 Polymere-cartridge


Carstick cartridges, Polymere-cartridge for compressed air applications Carstick®, Brass, 10 mm



### Product description

In line connection of tubing to a threaded port within a customised assembly. The assembly block must include cavities into which the cartridge can be fitted. Pre-greased and protected seal prior to assembly. Self-centring of the cartridge within the cavity. Suitable for automatic processes. Complies RoHS and ISO 14743.

### More images



**Product properties**

|                                        |                 |
|----------------------------------------|-----------------|
| <b>Weight in kg</b>                    | 0,005           |
| <b>Maximum working pressure in bar</b> | 20              |
| <b>max. temperature in °C</b>          | 80              |
| <b>min. temperature in °C</b>          | -20             |
| <b>RoHS compliant</b>                  | Yes             |
| <b>Vacuum resistance in mm Hg</b>      | 755             |
| <b>Material seal</b>                   | NBR             |
| <b>Material body</b>                   | Brass           |
| <b>Material toothed washer</b>         | Stainless steel |

**Dimensions**

|           |       |
|-----------|-------|
| <b>G</b>  | 15,5  |
| <b>G1</b> | 19,5  |
| <b>H</b>  | 17    |
| <b>L</b>  | 930   |
| <b>ØD</b> | 10 mm |