

## 3102 12 00 Equal and unequal elbows



LF 3000 standard pneumatic, Equal and unequal elbows, Engineered polymer, 12 mm -



### Product description

Connection at a 90° angle of 2 tubes of equal or different diameters. Prevents constriction of tube inner diameter. Solid construction, compact, aesthetic and unobtrusive for better connection. Full air flow. Individual unit quality control and dating in order to guarantee quality and traceability. Complies RoHS and ISO 14743.

### More images



**Product properties**

|                                        |                    |
|----------------------------------------|--------------------|
| <b>Weight in kg</b>                    | 0,01               |
| <b>Maximum working pressure in bar</b> | 20                 |
| <b>max. temperature in °C</b>          | 80                 |
| <b>min. temperature in °C</b>          | -20                |
| <b>RoHS compliant</b>                  | Yes                |
| <b>Vacuum resistance in mm Hg</b>      | 755                |
| <b>Material seal</b>                   | NBR                |
| <b>Material body</b>                   | Engineered polymer |
| <b>Material toothed washer</b>         | Stainless steel    |

**Dimensions**

|            |       |
|------------|-------|
| <b>G</b>   | 19    |
| <b>L</b>   | 40,5  |
| <b>ØD</b>  | 12 mm |
| <b>ØD1</b> | 12 mm |