

## 3109 06 10 Stud elbow


LF 3000 standard pneumatic, stud elbow, Engineered polymer, 6 mm - R1/8



### Product description

Connection of tubing at 90° with a male thread. Tightened on the top of the fitting with a flat spanner or Allen key to facilitate assembly in tight spaces. solid construction, aesthetic and unobtrusive for a better connection. Precoated thread ensuring direct sealing and full air flow. Individual unit quality control and dating in order to guarantee quality and traceability. Complies RoHS and ISO 14743.

### More images



## Product properties

|                                 |                     |
|---------------------------------|---------------------|
| Special feature                 | schwenkbar          |
| Seal coating                    | PTFE                |
| Weight in kg                    | 0,006               |
| Maximum working pressure in bar | 20                  |
| max. temperature in °C          | 80                  |
| min. temperature in °C          | -20                 |
| RoHS compliant                  | Yes                 |
| Vacuum resistance in mm Hg      | 755                 |
| Material seal                   | NBR                 |
| Material body                   | Engineered polymer  |
| Material threaded fitting       | Brass nickel plated |
| Material toothed washer         | Stainless steel     |

## Dimensions

|    |       |
|----|-------|
| C  | R1/8" |
| F  | 10    |
| G  | 10,5  |
| H  | 15,5  |
| L  | 16    |
| ØD | 6 mm  |