

Filter regulator Newdeal - 1425054


Filter regulator Newdeal, connection G 1/2", flow rate 1000 l/min., degree of filtration 20 µm, maximum inlet pressure 18 bar



Product description

Robust filter regulator made of metal.
Adjusted pressure stays constant despite pressure variations.
Standard overpressure blowoff valve.
Direct wall fixing or with distance.
Metal container with 360° viewing window.
Including pressure gauge.

More images



Product properties

Shielding	Technopolymer
Shielding plate	Technopolymer
Connection	Female thread G 1/2"
Container	Aluminium
Seals	NBR
Dome	Technopolymer
Flow rate in l/min	1000
Adjustment spring	Steel
Adjustment knob	Technopolymer
Adjusting nut	Brass Ms58
Adjusting screw	Brass Ms58
Filter element	HDPE
Filterfeinheit in µm	20
Weight in kg	1,114
Inner container	Transparent technopolymer
Piston	Technopolymer
Body	Zamac
Lip seal	NBR
max. inlet pressure	18
Ring nut	Technopolymer
Series	Newdeal
Bar	Brass Ms58
Plug	Technopolymer
Valve spring	Steel
Valve part	Vulcanized with NBR
Centrifuge	Technopolymer

Dimensions

A	60
B	245
C	60
D	60
EE	52
F	38 x 2
G	14
I	150
L	M4 suitable
M	185
N	1/8" pressure gauge connection
P	295