

D1 G3/8LH Fuel gas 0069-4002

Plug straight-through, coded system, female thread G 3/8LH, Fuel gas, <20 bar, stainless steel



Product description

Type D1 for torch side installation


The coupling pin D1 according to EN561, ISO 7289:

- no mixing up by different coding of coupling pins
- prevents accidental disconnection
- coupling pin in stainless steel
- swivel nut in brass 2.0401

Safety elements of the IBEDA Coupling pin D1:

- coding of coupling pins

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Female thread G 3/8LH
Connection description	Left-hand thread
Connection type	Female thread
Flat-sealing	No
Mould coupling	No
Gas types	Acetylene (A), Hydrogen (H), Industrial Gas (C), Natural Gas (Methane M), Propane (P)
Weight in kg	0,042
Hydraulics	No
Coded	Yes
Material	Stainless steel
Maximum working pressure in bar	1,5 (A), 20 (H, C, M, P)
Surface	blank finish
Professional recommendation	Gas safety technology, Coding
Series	D
Series long	D1
Standard product	No
Working temperature	-20°C up to +70°C
Water-resistant	No
Material connection	Brass
Additional information	Zulassungen / Technische Regeln / Richtlinien
Item number	0069-4002

Dimensions

Diameter in mm	21
Length in mm	47