

CLBA203 CellClutch cordless torque control angle nutrunner

Cordless angle nutrunner with torque control, torque 8,3 - 21 Nm, speed 36 - 360 1/min, 3/8" Square Drive



Product description


CellClutch cordless assembly tools enable simple, programmable torque control for your production.

CellClutch™ offers a torque control for functional screwdriving cases, and this is programmable for up to 7 levels to avoid errors when screwing in. The Tools have speed regulation and ensure long-term repeatability and accuracy in the screwing process.

- **Reduction of operating errors** – The presetting of the torque on the tool side and the screw status display using colored lights (green = OK, red = NOK) make it easier to handle the device correctly. Avoid errors when screwing in and double screwing with adjustable speeds and programmable screwing sequences.
- **Benefits of connectivity** – The optional WiFi (2.4 & 5 GHz) and Bluetooth Low Energy (v4.2) connectivity of the Connect models allows you to adjust settings, access real-time reports, data is tracked and counts are performed when the device is connected to the mPro Controller platform. A connection with a smartphone app is in preparation.
- **Uniform Battery Platform** – The Milwaukee® M18 Red Lithium battery is compatible with the entire battery products range. This enables economical storage of accessories.
- **Uncomplicated commissioning** – Setting the desired torque is a quick and easy process that consists of 3 steps: carry out a screw connection, read the torque and then make adjustments. Another screw connection serves to confirm that the target torque has been achieved.
- **Speed control** – The speed settings can be changed quickly and easily according to the requirements of the screwing job.
- **Ergonomic design** – The battery operation means there is no need for annoying cables and hoses. The low weight makes working easier.
- **Software included** – The software is already included when you purchase the tool at no additional cost.

Note: You can find suitable batteries and chargers in the accessories tab.

More images



Product properties

Output	3/8" Square Drive
Weight in kg	1,8
RoHS compliant	Yes
Maximum torque in Nm	21
Minimum torque in Nm	8,3
Maximum speed in 1/min	360
Minimum speed in 1/min	36
Precision	Cmk > 1.67 +/- 10%
Connectivity	Micro USB
Scope of delivery	Hanging bailTorque adjustment toolTorque detection rings black, gray, blueSocket, battery and charger are not included
Additional information	Software available as a free download

Dimensions

Height in mm	76
Length in mm	493
Side to center in mm	15