

NSA-392-8PL-E Plug with hose barb



Plug dry-break double shut-off, for Parker plug-in hose 10mm, nominal diameter 10, <20 bar, Aluminium anodized, seal EPDM



Product description

The NSA are dry-break quick couplings with FlatFace valves. Minimal fluid loss when uncoupling. NSA couplings exhibit minimal pressure drop and minimal air and dust entrapment during the coupling process.

More images



Product properties

Shut-off	Plug Dry-Break (double shut-off)
Connection	for Parker plug-in hose 10mm
Connection description	for Parker plug-in hose 10mm
Suitable breath / respiratory protection	No
Seal	EPDM
Seal description	Ethylene-propylene-diene rubber
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	Yes
Mould coupling	Yes
Weight in kg	0,047
Hydraulics	Yes
Coding	No
Material	Anodized aluminium
Bore in mm	10
Pneumatics	No
Professional recommendation	Flat-sealing
Safety locking system	No
Ultra-FLO-valve	No
Water-resistant	Yes
Two-hand operation	No
Working pressure	max. 20 bar
Series	NSA
Working temperature	-50°C to +175°C (fluorosilicone) depending on the flow medium. Special seals on request.
Advantages	Low weight due to aluminum construction. Leak-free. Push-Lok connection for time-saving assembly.

Dimensions