

M26KAKK12MPX Quick coupling with hose nut and spring guard





Quick coupling single shut-off, with hose nut and spring guard 9 x 12 mm, nominal diameter 7,2, <35 bar, brass, seal NBR



Product description

Universal brass coupling with European standard industrial profile. Coupling system with single-hand operation and standard-valve. Small mass size. The ergonomicsleeve design prevents dirt on the valve body.

More images



Product properties

Shut-off	Quick coupling Single Shut-Off
Connection	Tube nut with spring guard 9 x 12 mm
Connection description	Tube nut with spring guard 9 x 12 mm
Connection type	Connection nut
Suitable breath / respiratory protection	No
Seal	NBR
Seal description	Nitrite-butadiene rubber
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,1267
Hydraulics	No
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	40
Bore in mm	7,2
Surface	blank finish
Pneumatics	Yes
Series	26
Series long	26KA
Safety locking system	No
Standard product	No
Pin lock	Yes
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. European standard.
Water-resistant	Yes
Material connection	Brass
Material sleeve	Brass
Material spring	Spring steel
Material valve	Brass
Material valve body	Brass
Two-hand operation	No

Dimensions

Connection A	9 x 12 mm
D mm	25
G mm	M 16 x 1
L mm	127