

# M26KATS10MPN Quick coupling with hose barb in panel mount





Quick coupling single shut-off, panel mount with hose barb 10mm, nominal diameter 7,2, <35 bar, brass nickel plated, seal NBR



## Product description

Universal brass coupling with European standard industrial profile. Coupling system with single-hand operation and standard-valve. Small mass size. The ergonomicsleeve design prevents dirt on the valve body.

## More images



## Product properties

|                                          |                                        |
|------------------------------------------|----------------------------------------|
| Shut-off                                 | Quick coupling Single Shut-Off         |
| Connection                               | Hose barb in Panel mount 10mm          |
| Connection description                   | Hose barb in Panel mount 10mm          |
| Connection type                          | Hose barb                              |
| Suitable breath / respiratory protection | No                                     |
| Seal                                     | NBR                                    |
| Seal description                         | Nitrite-butadiene rubber               |
| Pressure eliminator                      | No                                     |
| Single-hand operation                    | Yes                                    |
| Self-venting coupling                    | No                                     |
| Flat-sealing                             | No                                     |
| Mould coupling                           | No                                     |
| Weight in kg                             | 0,0879                                 |
| Hydraulics                               | No                                     |
| Ball locking                             | No                                     |
| Material                                 | Brass nickel plated                    |
| Material description                     | Brass CuZn39Pb3 2.0401 (except sleeve) |
| Bore area in mm <sup>2</sup>             | 40                                     |
| Bore in mm                               | 7,2                                    |
| Surface                                  | nickel plated                          |
| Pneumatics                               | Yes                                    |
| Series                                   | 26                                     |
| Series long                              | 26KA                                   |
| Safety locking system                    | No                                     |
| Standard product                         | No                                     |
| Pin lock                                 | Yes                                    |
| Ultra-FLO-valve                          | No                                     |
| Vacuum suitable                          | Yes                                    |
| Advantages                               | One-hand operation. European standard. |
| Water-resistant                          | Yes                                    |
| Material connection                      | Brass nickel plated                    |
| Material sleeve                          | Brass nickel plated                    |
| Material spring                          | Spring steel                           |
| Material valve                           | Brass                                  |
| Material valve body                      | Brass nickel plated                    |
| Two-hand operation                       | No                                     |

## Dimensions

|              |       |
|--------------|-------|
| Connection A | 10 mm |
| B mm         | 4     |
| D mm         | 25    |
| L mm         | 70    |
| L1 mm        | 25    |
| L2 mm        | 14    |
| SW mm        | 22    |