

## M21KBTF04MPX Quick coupling with hose barb




Quick coupling double shut-off, hose barb 4mm (3/16), nominal diameter 5, <35 bar, brass, seal NBR



### Product description

Mini industrial coupling with the world's most popular profile in this nominal diameter. Above average flow performance for liquid and gaseous medio. Coupling system with single-hand operation. Small dimensions and large band width in materials and valve variants.

### More images



## Product properties

|                                          |                                        |
|------------------------------------------|----------------------------------------|
| Shut-off                                 | Quick coupling Double Shut-Off         |
| Connection                               | Hose barb 4mm LW(3/16")                |
| Connection description                   | Hose barb 4mm LW(3/16")                |
| Connection type                          | Hose barb                              |
| Suitable breath / respiratory protection | No                                     |
| Seal                                     | NBR                                    |
| Seal description                         | Nitrite-butadiene rubber               |
| Pressure eliminator                      | No                                     |
| Single-hand operation                    | Yes                                    |
| Self-venting coupling                    | No                                     |
| Flat-sealing                             | No                                     |
| Mould coupling                           | No                                     |
| Weight in kg                             | 0,027                                  |
| Hydraulics                               | No                                     |
| Ball locking                             | Yes                                    |
| Material                                 | Brass                                  |
| Material description                     | Brass CuZn39Pb3 2.0401 (except sleeve) |
| Bore area in mm <sup>2</sup>             | 20                                     |
| Bore in mm                               | 5                                      |
| Surface                                  | blank finish                           |
| Pneumatics                               | Yes                                    |
| Series                                   | 21                                     |
| Series long                              | 21KB                                   |
| Safety locking system                    | No                                     |
| Standard product                         | No                                     |
| Pin lock                                 | No                                     |
| Ultra-FLO-valve                          | No                                     |
| Vacuum suitable                          | Yes                                    |
| Advantages                               | One-hand operation. Small dimensions.  |
| Water-resistant                          | Yes                                    |
| Material connection                      | Brass                                  |
| Material sleeve                          | Brass                                  |
| Material spring snap ring                | stainless steel AISI 301               |
| Material valve                           | Brass                                  |
| Material valve body                      | Brass                                  |
| Two-hand operation                       | No                                     |

## Dimensions

|              |      |
|--------------|------|
| Connection A | 4 mm |
| D mm         | 16   |
| L mm         | 46   |
| L1 mm        | 17   |
| SW mm        | 14   |