

M26KAAW21MPXS_36 Quick coupling with male thread





Quick coupling single shut-off, male thread G 1/2, nominal diameter 7,2, <35 bar, brass, seal NBR



Product description

Universal brass coupling with European standard industrial profile. Coupling system with single-hand operation and standard-valve. Small mass size. The ergonomicsleeve design prevents dirt on the valve body.

More images



Product properties

Shut-off	Quick coupling Single Shut-Off
Connection	Male thread 1/2"
Connection description	Male pipe thread of Whitworth form ISO 228 1/2
Connection type	Male thread
Suitable breath / respiratory protection	No
Seal	NBR
Seal description	Nitrite-butadiene rubber
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,0913
Hydraulics	No
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm²	40
Bore in mm	7,2
Surface	blank finish
Pneumatics	Yes
Professional recommendation	Pneumatic standard
Series	26
Series long	26KA
Safety locking system	No
Special variant	Yes
Special variant description	S=SW24 COUPLING
Standard product	Yes
Pin lock	Yes
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. European standard.
Water-resistant	Yes
Material connection	Brass
Material sleeve	Brass
Material spring	Spring steel
Material valve	Brass
Material valve body	Brass
Two-hand operation	No

Dimensions

Connection A	G 1/2
D mm	25
L mm	41
L1 mm	10
SW mm	24