

## M26SFIW10MXX Plug with female thread





Plug straight-through, female thread G 1/8, nominal diameter 7,2, <35 bar, brass



### Product description

Universal brass coupling with European standard industrial profile. Coupling system with single-hand operation and standard-valve. Small mass size. The ergonomic sleeve design prevents dirt on the valve body.

### More images



#### Product properties

|                                                 |                                                   |
|-------------------------------------------------|---------------------------------------------------|
| <b>Shut-off</b>                                 | Plug Straight-Through                             |
| <b>Connection</b>                               | Female thread 1/8"                                |
| <b>Connection description</b>                   | Female pipe thread of Whitworth form ISO 228 1/8" |
| <b>Connection type</b>                          | Female thread                                     |
| <b>Suitable breath / respiratory protection</b> | No                                                |
| <b>Seal</b>                                     | Without Seal                                      |
| <b>Pressure eliminator</b>                      | No                                                |
| <b>Single-hand operation</b>                    | Yes                                               |
| <b>Self-venting coupling</b>                    | No                                                |
| <b>Flat-sealing</b>                             | No                                                |
| <b>Mould coupling</b>                           | No                                                |
| <b>Hydraulics</b>                               | No                                                |
| <b>Ball locking</b>                             | No                                                |
| <b>Material</b>                                 | Brass                                             |
| <b>Material description</b>                     | Brass CuZn39Pb3 2.0401 (except sleeve)            |
| <b>Bore area in mm<sup>2</sup></b>              | 40                                                |
| <b>Bore in mm</b>                               | 7,2                                               |
| <b>Surface</b>                                  | blank finish                                      |
| <b>Pneumatics</b>                               | Yes                                               |
| <b>Professional recommendation</b>              | Pneumatic standard                                |
| <b>Series</b>                                   | 26                                                |
| <b>Series long</b>                              | 26SF                                              |
| <b>Safety locking system</b>                    | No                                                |
| <b>Standard product</b>                         | No                                                |
| <b>Pin lock</b>                                 | No                                                |
| <b>Ultra-FLO-valve</b>                          | No                                                |
| <b>Vacuum suitable</b>                          | Yes                                               |
| <b>Advantages</b>                               | One-hand operation. European standard.            |
| <b>Water-resistant</b>                          | Yes                                               |
| <b>Two-hand operation</b>                       | No                                                |

#### Dimensions

|                     |       |
|---------------------|-------|
| <b>Connection A</b> | G 1/8 |
| <b>L mm</b>         | 30    |
| <b>SW mm</b>        | 13    |