

## M26SFIW17MXN Plug with female thread





Plug straight-through, female thread G 3/8, nominal diameter 7,2, <35 bar, brass nickel plated



### Product description

Universal brass coupling with European standard industrial profile. Coupling system with single-hand operation and standard-valve. Small mass size. The ergonomicsleeve design prevents dirt on the valve body.

### More images



#### Product properties

|                                          |                                                   |
|------------------------------------------|---------------------------------------------------|
| Shut-off                                 | Plug Straight-Through                             |
| Connection                               | Female thread 3/8"                                |
| Connection description                   | Female pipe thread of Whitworth form ISO 228 3/8" |
| Connection type                          | Female thread                                     |
| Suitable breath / respiratory protection | No                                                |
| Seal                                     | Without Seal                                      |
| Pressure eliminator                      | No                                                |
| Single-hand operation                    | Yes                                               |
| Self-venting coupling                    | No                                                |
| Flat-sealing                             | No                                                |
| Mould coupling                           | No                                                |
| Weight in kg                             | 0,0239                                            |
| Hydraulics                               | No                                                |
| Ball locking                             | No                                                |
| Material                                 | Brass nickel plated                               |
| Material description                     | Brass CuZn39Pb3 2.0401 (except sleeve)            |
| Bore area in mm <sup>2</sup>             | 40                                                |
| Bore in mm                               | 7,2                                               |
| Surface                                  | nickel plated                                     |
| Pneumatics                               | Yes                                               |
| Series                                   | 26                                                |
| Series long                              | 26SF                                              |
| Safety locking system                    | No                                                |
| Standard product                         | No                                                |
| Pin lock                                 | No                                                |
| Ultra-FLO-valve                          | No                                                |
| Vacuum suitable                          | Yes                                               |
| Advantages                               | One-hand operation. European standard.            |
| Water-resistant                          | Yes                                               |
| Two-hand operation                       | No                                                |

#### Dimensions

|              |       |
|--------------|-------|
| Connection A | G 3/8 |
| L mm         | 31,5  |
| SW mm        | 19    |