

## M26SFAN13MXX Plug with male thread





Plug straight-through, male thread NPT 1/4, nominal diameter 7,2, <35 bar, brass



### Product description

Universal brass coupling with European standard industrial profile. Coupling system with single-hand operation and standard-valve. Small mass size. The ergonomic sleeve design prevents dirt on the valve body.

### More images



#### Product properties

|                                          |                                        |
|------------------------------------------|----------------------------------------|
| Shut-off                                 | Plug Straight-Through                  |
| Connection                               | Male thread NPT 1/4"                   |
| Connection description                   | Male NPT thread ANSI B 1.20.1 1/4"     |
| Connection type                          | Male thread                            |
| Suitable breath / respiratory protection | No                                     |
| Seal                                     | Without Seal                           |
| Pressure eliminator                      | No                                     |
| Single-hand operation                    | Yes                                    |
| Self-venting coupling                    | No                                     |
| Flat-sealing                             | No                                     |
| Mould coupling                           | No                                     |
| Weight in kg                             | 0,023                                  |
| Hydraulics                               | No                                     |
| Ball locking                             | No                                     |
| Material                                 | Brass                                  |
| Material description                     | Brass CuZn39Pb3 2.0401 (except sleeve) |
| Bore area in mm <sup>2</sup>             | 40                                     |
| Bore in mm                               | 7,2                                    |
| Surface                                  | blank finish                           |
| Pneumatics                               | Yes                                    |
| Series                                   | 26                                     |
| Series long                              | 26SF                                   |
| Safety locking system                    | No                                     |
| Standard product                         | No                                     |
| Pin lock                                 | No                                     |
| Ultra-FLO-valve                          | No                                     |
| Vacuum suitable                          | Yes                                    |
| Advantages                               | One-hand operation. European standard. |
| Water-resistant                          | Yes                                    |
| Two-hand operation                       | No                                     |

#### Dimensions

|       |    |
|-------|----|
| L mm  | 36 |
| L1 mm | 12 |
| SW mm | 14 |