

M20SFAM05RXX Plug with male thread




Plug straight-through, male thread M 5, nominal diameter 2,7, <35 bar, stainless steel AISI 303



Product description

Mini industrial coupling with internationally used profile. Frequent use in medical technology and chemistry/pharmacy. Coupling system with single-hand operation. High flow despite small dimensions plus many applications with a variety of medio.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Male thread M 5
Connection description	Male thread metric DIN 13 M 5
Connection type	Male thread
Suitable breath / respiratory protection	No
Seal	Without Seal
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,003
Hydraulics	No
Compatibility	RECTUS 91
Ball locking	No
Material	stainless steel AISI 303
Material description	stainless steel AISI 303
Bore area in mm ²	6
Bore in mm	2,7
Surface	blank finish
Pneumatics	Yes
Series	20
Series long	20SF
Safety locking system	No
Standard product	No
Pin lock	No
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. Small dimensions.
Water-resistant	Yes
Two-hand operation	No

Dimensions

Connection A	M 5
L mm	18
L1 mm	5
SW mm	7