

## NSSC-1001-20MBE Screw coupling with male thread



Screw coupling dry-break double shut-off, male thread 1 1/4", nominal diameter 25, <10 bar, galvanized steel/stainless steel, seal EPDM



### Product description

NSSC couplings are the right solution for connection under pressure. The NSSC couplings are a screw to connect dry-break couplings with flat face valves.

### More images



#### Product properties

|                                          |                                  |
|------------------------------------------|----------------------------------|
| Suitable breath / respiratory protection | No                               |
| Seal                                     | EPDM                             |
| Seal description                         | Ethylene-propylene-diene rubber  |
| Pressure eliminator                      | No                               |
| Single-hand operation                    | No                               |
| Self-venting coupling                    | No                               |
| Flat-sealing                             | Yes                              |
| Mould coupling                           | Yes                              |
| Weight in kg                             | 0,6                              |
| Hydraulics                               | Yes                              |
| Coding                                   | No                               |
| Material                                 | Galvanized steel/stainless steel |
| Bore in mm                               | 25                               |
| Pneumatics                               | No                               |
| Professional recommendation              | Flat-sealing                     |
| Safety locking system                    | No                               |
| Ultra-FLO-valve                          | No                               |
| Water-resistant                          | Yes                              |
| Two-hand operation                       | Yes                              |

#### Dimensions

|              |         |
|--------------|---------|
| Connection A | G 1 1/4 |
| D mm         | 56      |
| L mm         | 93      |
| L1 mm        | 20      |
| SW mm        | 50      |