

Balancer 77001009

Hose balancer, payload range 0,4 - 1,2 kg, cable length 0,8 m, with quick coupling and hose tail 6 mm, air connection R 1/4"i.



Product description

Hose balancer for industrial applications.

Hanging with a turnable screwing carabiner.

Casing and cable drum are made of shockproof and abrasion-resistant plastic, red-orange.

Casing lid made of sheet steel, painted.

High-strength and sturdy (damage-resistant) air hose with inner width of 6 mm and attached quick coupling.

Air supply through R1/4" female thread on the casing.

The working stroke can be infinitely variable shortened.

High-strength riveted special mainspring.

Longer hose available on demand.

The hose stop buffer is infinitely variable adjustable.

Maximum working pressure: 10 bar

Air passage: 860 l/min at 6 bar.

More images

Product properties

Fall protection	Existing, according to DIN 15112
Connection (casing)	Female thread R 1/4"
Connection (hose)	Quick coupling and plug 6 mm
Locking	No
Suspension	Turnable and traversable screwing carabiner
Spring fracture protection	No
Weight in kg	1,7
Material casing	Shockproof and abrasion-resistant plastic
Maximum working pressure in bar	10
max. inlet pressure	10
Cable stop	Yes, shock absorbing and adjustable
Payload range in kg	0,4 - 1,2
Load setting	by screening mit Allen key
Additional information	Air flow rate is identical in withdrawn and extended state of the hose.
Series	8223

Dimensions

Colour	Orange
Hose Inner diameter in mm	6
Cable length in m	0,8